



COMPRESSORS



## BOOSTER

<b>MODEL</b>	: 524 KANOPI	
<b>PURPOSE OF USAGE</b>	: Compressed Air/Gas	
<b>INLET PRESSURE</b>	: 8 Bar	
<b>WORKING PRESSURE</b>	: 40 Bar (580 psi)	
<b>CAPACIYT</b>	: 2500 lt/min (150 m3/h)	: 3400 lt/min (204 m3/h)
<b>MOTOR POWER</b>	: 11 kW (15 Hp)	: 15 kW (20 Hp)
<b>COMPRESSOR SPEED</b>	: 670 r/min	: 800 r/min
<b>NUMBER OF STAGE</b>	: 1	
<b>NUMBER OF CYLINDER</b>	: 2	
<b>LUBRICATION SYSTEM</b>	: Impact Lubrication	
<b>POWER TRANSMISSION</b>	: Belt-Pulley	
<b>OPERATING TEMP RANGE</b>	: 0...+50 °C	
<b>DIMENSIONS (WxLxH)</b>	: 770 x 1110 x 1600 mm	
<b>WEIGHT</b>	: 440 kg	: 450 kg

### STANDART EQUIPMENT

Intercooler
Safety Valve at Each Stage
Check valve
Manometers Showing Inlet and Outlet Pressure
Pressure Automatic for Automatic Start/Stop
Discharge Solenoid
Oil Level Switch
Electrostatic Painted Chassis
Oil Level Sight Gauge
Thermal Overload Protection for Electric Motor
Vibration Mounts

### OPTIONAL

PLC Touch Screen Control System
Stainless Chassis