

**BOOSTER**

<b>MODEL</b>	: 526 CANOPY	
<b>INTENDED USE</b>	: Compressed Air/Gas	
<b>INLET PRESSURE</b>	: 8 Bar	
<b>WORKING PRESSURE</b>	: 40 Bar (580 psi)	
<b>CAPACITY</b>	: 5000 l/min (300 m3/h)	6000 l/min (360 m3/h)
<b>MOTOR POWER</b>	: 18,5 kW (25 Hp)	22 kW (30 Hp)
<b>COMPRESSOR SPEED</b>	: 750 rpm	840 rpm
<b>NUMBER OF STAGE</b>	: 1	
<b>NUMBER OF CYLINDER</b>	: 3	
<b>LUBRICATION SYSTEM</b>	: Forced Lubrication	
<b>POWER TRANSMISSION</b>	: Belt-Pulley	
<b>WORKING TEMP.RANGE</b>	: 0...+50 °C	
<b>DIMENSIONS (WxLxH)</b>	: 770 x 1200 x 1720 mm	
<b>WEIGHT</b>	: 630 kg	640 kg
<b>STANDARD EQUIPMENT</b>		
Aftercooler		
Safety Valve at Each Stage		
Check Valve		
Manometers Showing Inlet and Outlet Pressure		
Pressure Switch for Automatic Start/Stop		
Solenoid Valve		
Oil Level Switch		
Electrostatic Painted Chassis		
Oil Level Sight Gauge		
Thermal Overload Protection for Electric Motor		
Shock Mounts		
<b>OPTIONAL</b>		
PLC Touch Screen Control System		
Stainless Chassis		