



MEDIUM PRESSURE AIR COMPRESSOR

MODEL	: 526	
PURPOSE OF USAGE	: Compressed Air	
FILTER SYSTEM	: Optional	
WORKING PRESSURE	: 40 Bar (580 psi)	
CAPACITY	: 1715 lt/min (103 m3/h)	2010 lt/min (121 m3/h)
MOTOR POWER	: 15 kW	18,5 kW
COMPRESSOR SPEED	: 640 r/min	750 r/min
NUMBER OF STAGE	: 2	
NUMBER OF CYLINDER	: 3	
LUBRICATION SYSTEM	:Impact Lubrication	
POWER TRANSMISSION	: Belt-Pulley	
OPERATING TEMP RANGE	: 0...+50 °C	
DIMENSIONS (WxLxH)	: 770 x 1200 x 1720 mm	
WEIGHT	: 630 kg	640 kg
STANDART EQUIPMENT		
Inter and After Cooler Pipes (Stainless)		
Water and Oil Separator		
Safety Valve at Each Stage		
Check Valve		
Manometers Showing Inlet and Outlet Pressure		
Pressure Automatic for Automatic Start/Stop		
Discharge Solenoid		
Oil Level Switch		
Electrostatic Painted Chassis		
Oil Level Sight Gauge		
Thermal Overload Protection for Electric Motor		
Vibration Mounts		
OPTIONAL		
PLC Touch Screen Control System		
Stainless Chassis		