



MEDIUM PRESSURE AIR COMPRESSOR

MODEL	: 528			
INTENDED USE	: Compressed Air			
FILTER SYSTEM	: Optional			
WORKING PRESSURE	: 70 Bar (1015 psi)			
DISPLACEMENT CAPACITY	1200 l/min (56 m3/h)	1360 l/min (81m3/h)	1410 l/min (84m3/h)	1460 l/min (87m3/h)
MOTOR POWER	: 11 kW	: 15 kW	: 15 kW	: 18,5 kW
COMPRESSOR SPEED	: 740 rpm	: 840 rpm	: 870 rpm	: 900 rpm
NUMBER OF STAGES	: 3			
NUMBER OF CYLINDERS	: 3			
LUBRICATION SYSTEM	: Forced Lubrication			
POWER TRANSMISSION	: Belt-Pulley			
OPERATING TEMP RANGE	: 0...+50 °C			
DIMENSIONS (WxLxH)	: 770 x 1290 x 1720 mm			
WEIGHT	: 650 kg	: 660 kg	: 660 kg	: 670 kg
STANDARD EQUIPMENT				
Inter and After Cooler Pipes (Stainless)				
Water and Oil Separator				
Safety Valve at Each Stage				
Check Valve				
Manometers Showing Inlet and Outlet Pressure				
Pressure Automatic for Automatic Start/Stop				
Discharge Solenoid				
Oil Level Switch				
Electrostatic Painted Chassis				
Oil Level Sight Gauge				
Thermal Overload Protection for Electric Motor				
Shock Mounts				
OPTIONAL				
PLC Touch Screen Control System				
Stainless Chassis				