



COMPRESSORS



BOOSTER

MODEL	: 530		
PURPOSE OF USAGE	: Compressed Air/Gas		
INPUT PRESSURE	: 8 Bar		
WORKING PRESSURE	: 40 Bar (580 psi)		
CAPACITY	: 2800 lt/min	: 3800 lt/min	: 4800 lt/min
MOTOR POWER	: 11 kW (15 Hp)	: 15 kW (20 Hp)	: 18,5 kW (25 Hp)
COMPRESSOR SPEED	: 600 r/min	: 800 r/min	: 1000 r/min
NUMBER OF STAGE	: 1		
NUMBER OF CYLINDER	: 3		
LUBRICATION SYSTEM	: Impact Lubrication		
POWER TRANSMISSION	: Belt-Pulley		
WORKING TEMP. RANGE	: 0...+50 °C		
DIMENSIONS (WxLxH)	: 770 x 870 x 1310 mm		
WEIGHT	: 410 kg	: 420 kg	: 430 kg

STANDART DONANIM

- Intercooler
- Pressure Automatic for Automatic Start/Stop
- Safety Valve at Each Stage
- Automatic Discharge Solenoid
- Oil Level Switch
- Oil Level Sight Gauge
- Electrostatic Painted Chassis
- Giriş ve Çıkış Manometresi
- Thermal Overload Protection for Electric Motor
- Vibration Mounts

OPTIONAL

- PLC Touch Screen Control System
- Stainless Chassis