

**MEDIUM PRESSURE AIR COMPRESSOR**

MODEL	: 702 - Chassis	
PURPOSE OF USAGE	: Compressed Air	
FILTER SYSTEM	: -	
WORKING PRESSURE	: 40 Bar (580 psi)	
DISPLACEMENT CAPACITY	1090 lt/min (65,5 m3/h)	1440 lt/min (86,5 m3/h)
MOTOR POWER	11 kW (15 Hp)	15 kW (20 Hp)
COMPRESSOR STAGE	830 r/min	1100 r/min
1nd ST PRESSURE RANGE	: 4 - 7 Bar	
2. KAD. BASINÇ ARALIĞI	: Output Pressure (40 Bar)	
NUMBER TO STAGE	: 2	
NUMBER TO CYLINDER	: 3	
LUBRICATION SYSTEM	: Impact Lubrication	
POWER TRANSMİSSİON	: Belt-Pulley	
WORKING TEMP.RANGE	: 0...+50 °C	
DIMENSIONS (WxLxH)	: 760 x 1300 x 860 mm	
WEIGHT	325 kg	335 kg
STANDART EQUIPMENT		
Inter and After Cooler Pipes (Stainless)		
Water and Oil Separator		
Safety Valve at Each Stage		
Check Valve		
Manometers Showing Inlet and Outlet Pressure		
Pressure Automatic for Automatic Start/Stop		
Discharge Solenoid		
Stainless Chassis		
Electrostatic Painted Portable Chassis		
Oil Level Sight Gauge		
Thermal Overload Protection for Electric Motor		
Vibration Mounts		
Control and Electrical panel: YΔ Panel, Main Switch, On/Off Buttons, Hour Counter, Emergency Stop Buttons, Control Leds		
OPTIONAL		
PLC Touch Screen Control System		
Stainless Chassis		