

**HIGH PRESSURE AIR COMPRESSOR**

| | |
|--|----------------------------------|
| MODEL | : W3 - CANOPY |
| INTENDED USE | : Compressed Air / Breathing Air |
| FILTER SYSTEM | : Filter+P61 |
| WORKING PRESSURE | : 150 Bar (2175 psi) |
| MAX. WORKING PRESSURE | : 150 Bar |
| CAPACITY | : 1050 l/min |
| MOTOR POWER | : 22 kW (30 Hp) |
| COMPRESSOR SPEED | : 740 rpm |
| 1st STG PRESSURE RANGE | : - |
| 2nd STG PRESSURE RANGE | : - |
| 3rd STG PRESSURE RANGE | : Outlet Pressure |
| NUMBER TO STAGE | : 3 |
| NUMBER TO CYLINDER | : 3 |
| LUBRICATION SYSTEM | : Forced Lubrication |
| POWER TRANSMISSION | : Belt-Pulley |
| WORKING TEMP.PRESSURE | : 0...+50 °C |
| DIMENSIONS (WxLxH) | : 1000 x 1310 x 1720 mm |
| WEIGHT | : 700 kg |
| STANDARD EQUIPMENT | |
| P61 Purifier and Refillable Cartridge | |
| Particle and Oil Holder Filter (Stainless) | |
| 2nd and 3rd Stage Water Separator | |
| Intercooler Radiator, Inter and After Cooler Pipes (Stainless) | |
| Safety Valve at Each Stage | |
| Silencer Filter | |
| Priority Valve - Check Valve | |
| Oil Level Glass - Oil Level Switch | |
| Automatic Start/Stop and Drain | |
| Electrostatic Painted Silent Canopy | |
| Breathing Air Quality Complies with EN 12021:2014 | |
| OPTIONAL | |
| PLC Touch Screen Control System | |
| Stainless Canopy | |
| Extra Filling Hose | |
| Replaceable (Disposable) Cartridge | |