

VİDALI HAVA KOMPRESÖRLERİ

COMPRESORES DE TORNILLO AEREO

AIR SCREW COMPRESSORS



- Special sound insulation
Aislamiento acústico especial
Özel ses izolasyonu
- PLC control unit
Unidad de control PLC
PLC kontrol ünitesi
- Oil-air separator tank
Tanque separador de aire y aceite
Yağ hava seperatör tankı
- Oil filter and thermostatic valve carrier
Filtro de aceite y soporte de
válvula termostática
Yağ filtresi ve termostatik valf takozu
- Aluminium radiators
Radiador de aluminio
Alüminyum radyatör
- High efficient cooling fan
Ventiladores de enfriamiento
de alta eficiencia
Yüksek verimli soğutma fanları
- Belt tensioning mechanism
Tensor de correa
Kayış ve gergi sistemi

From 3 kW to 250 kW
De 3 kW a 250 kW
3 kW'tan 250 kW'a kadar

TECHNICAL SPECIFICATIONS / DATOS TÉCNICAS / TEKNİK ÖZELLİKLERİ

MODEL MODELO	CAPACITY / CAPACIDAD KAPASİTE (m ³ /dak)			MOTOR POWER MOTOR MOTOR GÜCÜ (kW / hp)	VOLTAGE FASE DE VOLTAJE VOLTAJ FAZ (volt)	AIR OUTLET SALIDE DE AIRE HAVA ÇIKIŞI (inch)	DIMENSIONS DIMENSIONES ÖLÇÜLER (en x boy x yüks.) (mm)
	7 Bar	10 Bar	13 Bar				
ALK-3	0.42	0.35	0.29	3/4	400/3	1/2"	500x750x620
ALK-3 M	0.42	0.35	0.29	3/4	230/1	1/2"	500x750x620
ALK-4	0.58	0.46	0.40	4/5,5	400/3	1/2"	500x750x620
ALK-5,5	0.80	0.68	0.57	5,5/7,5	400/3	3/4"	643x818x865
ALK-7,5	1.10	0.90	0.70	7,5/10	400/3	3/4"	643x818x865
ALK-11	1.70	1.30	1.10	11/15	400/3	3/4"	643x818x865
ALK-15	2.50	2.10	1.75	15/20	400/3	1"	810x1170x1370
ALK-18,5	3.10	2.60	2.20	18,5/25	400/3	1"	810x1170x1370
ALK-22	3.60	3.10	2.75	22/30	400/3	1"	810x1170x1370
ALK-30	5.10	4.30	3.85	30/40	400/3	1 1/4"	895x1330x1700
ALK-37	6.30	5.20	4.30	37/50	400/3	1 1/2"	895x1330x1700
ALK-45	7.00	6.20	5.70	45/60	400/3	1 1/2"	895x1330x1700
ALK-55	9.60	8.00	7.00	55/75	400/3	2"	1165x1670x1800
ALK-75	12.30	10.70	8.80	75/100	400/3	2"	1165x1670x1800

Serbest hava verimleri ISO 1217 Ek C Standartına göre ölçülmüş olup, giriş hava sıcaklığı 20°C giriş hava basıncı 1 bar'dır.