



HIGH PRESSURE AIR COMPRESSOR

MODEL	: W32 - CANOPY BOOSTER		
PURPOSE OF USAGE	: Compressed Gas		
FILTER SYSTEM	: P41		
WORKING PRESSURE	: 225 Bar (3260 psi)		
MAX. WORKING PRESSURE	: 350 Bar		
CAPACITY	: 250 lt/min	: 300 lt/min	: 350 lt/min
MOTOR POWER	: 4 kW (5,5 Hp)	: 5,5 kW (7,5 Hp)	: 7,5 kW (10 Hp)
COMPRESSOR SPEED	: 1250 r/min	: 1350 r/min	: 1500 r/min
1. ST. PRESSURE RANGE	: 5 - 20 Bar		
2. ST. PRESSURE RANGE	: 20-60 Bar		
3. ST. PRESSURE RANGE	: Output Pressure		
NUMBER OF STAGE	: 3		
NUMBER OF CYLINDER	: 3		
LUBRICATION SYSTEM	: Pump Lubrication		
POWER TRANSMISSION	: Belt-Pulley		
WORKING TEMP. RANGE	: 0...+50 °C		
DIMENSIONS (WxLxH)	: 700 x 1030 x 1300 mm		
WEIGHT	: 280 kg	: 290 kg	: 300 kg
STANDART EQUIPMENT			
P41 Purifier and Refillable Cartridge			
2nd and 3rd Stage Water Separator			
Intercooler			
Aftercooler			
Priority Valve , Check Valve			
Safety Valve at Each Stage			
Oil Indicator Glass - Oil Level Switch			
Vibration Mounts			
Manuel Start - Stop - Discharge			
Thermal Overload Protection for Electric Motor			
Control Panel: On Off Buttons, Hour Counter			
Electrostatic Painted Portable Chassis			
OPTIONAL			
Automatic Start - Stop - Discharge			
Stainless Chassis			
Replaceable (Disposable) Cartridge			